



型号	组合尺寸(mm)				滑座尺寸(mm)							滑轨尺寸(mm)			
	H	W	W2	E	L	B×J	MQ×L	L1	油孔	T1	N	W1	H1	F	d×D×h
BRH15A	24	47	16	4.6	66	38×30	M5×8	40	∅3	4.3	5	15	14	60	4.5×7.5×5.3
BRH20A	30	63	21.5	5	77.8	53×40	M6×9	48.8	M6×1	5	6.5	20	18	60	6×9.5×8.5
BRH20AL					92.4			63.4							
BRH25A	36	70	23.5	7	88	57×45	M8×12	57	M6×1	5	6.5	23	22	60	7×11×9
BRH25AL					110.1			79.1							
BRH30A	42	90	31	9	109	72×52	M10×12	72	M6×1	7	6.5	28	26	80	9×14×12
BRH30AL					131.3			94.3							
BRH35A	48	100	33	9.5	119	82×62	M10×13	80	M6×1	8	6.5	34	29	80	9×14×12
BRH35AL					144.8			105.8							
BRH45A	60	120	37.5	14	148.2	100×80	M12×15	105	M8×1	10	13	45	38	105	14×20×17
BRH45AL					173			129.8							
BRH55A	70	140	43.5	15	170	116×95	M14×20	121	M8×1	11	13	53	44	120	16×23×20
BRH55AL					205.1			156.1							

型号	参考资料(mm)		基本荷重(kgf)		容许静力矩(kgf*m)			重量(mm)	
	L max	G	动额定负荷(G)	静额定负荷(G)	Mx	My	Mz	滑块(kgf)	滑轨(kgf/M)
BRH15A	4000	20	850	1650	10	8	8	0.19	1.4
BRH20A	4000	20	1450	2650	22	18	18	0.4	2.6
BRH20AL			1900	3330	28.6	23.4	23.4	0.52	
BRH25A	4000	20	2140	4000	36	32	31	0.57	3.6
BRH25AL			2996	5600	50.4	44.8	43.4	0.72	
BRH30A	4000	20	2980	5490	60	50	49	1.1	5.2
BRH30AL			5230	9270	125	95	95	2	
BRH35A	4000	20	3960	7010	96	75	73	1.6	7.2
BRH35AL			5230	9270	125	95	95	2	
BRH45A	4000	22.5	6740	12100	216	170	168	2.7	12.3
BRH45AL			8330	14950	267	210	210	3.6	
BRH55A	4000	30	9940	17100	367	293	288	5	16.9
BRH55AL			12820	22060	473	380	375	6.4	